



TULSA

Plywood

Film Premium

PHENOLIC FILM PANEL

Overlaid film for concrete form
Panel overlaid both sides with black film PSF
125 g/m² + MDO 235 g/m². 15 to 25 uses per
face.

GENERAL SPECIFICATIONS

- Allows between 30 to 50 reuses (requires reasonable care).
- Faces have 125 g/m² phenolic film overlay + 235 m/m MDO film overlay, with a total of 360 g/m² providing a high quality that assures water resistance and stiffness stability.
- 65% Phenolic resin in overlay film and 27% in MDO.

PRODUCT FEATURES AND APPLICATIONS

Tulsa Premium Overlay Panel are edge sealed during manufacturing. If you have to cut boards during the use, it is recommended to re-seal the fresh edges to avoid panel damage caused by capillary penetration of humidity.

Make sure to also use the appropriate form remover or release agent (a chemical reactive releases for nonporous surfaces).

Although cleaning a Tulsa Premium Panel is much easier and quicker than traditional form materials, it is important to only use fiber spatulas and synthetic materials when cleaning forms to prevent damage to the faces. This damage might occur when using metallic tools. Always store the panels inside a warehouse, protected from weather conditions.

While Tulsa Premium Overlay Panel are very resistant to the abrasion and impact, care must be taken during cleaning and use to prevent damage. Always use the appropriate vibrators and techniques to protect panel's surface.

